



DX3515

ASI TS Switcher



Product Overview

DX3515 TS switcher supports 3 ASI input and 2 ASI out and switch manually or automatically. It can realize a TS seamless switching by turning back to the main stream manually or automatically once the main stream recovers. This unit is widely applied to DTV signal backup system.

Key Features

- **3 ASI input: ASI 3 is main stream, ASI 2 is secondary stream (backup 1), ASI 1 is third stream (back up 2).**
- **2 ASI output: ASI 4 output bypass, ASI 5 loop out ASI 3**
- **Support manually and automatically switching**
- **Support channel mode and program mode switching**
- **Support to switch back to the main stream manually or automatically once the main stream recovers**
- **Support 188 format TS packet**
- **Support monitor program status (bitrate, continuous counting, synchronization status)**
- **Support web-server management (WEB)**



All the specifications are subject to change without any further notice. All rights reserved.

Add: No. 10 & No. 12, Wuxing Fourth Road, Wuhou District, Chengdu 610045, Sichuan, P.R. China
www.dsdvb.com/English Tel: +86-028-85558928 Fax: +86-028-85585255 Email: sunyu@dsdvb.com

Specifications

Input	3 ASI input: ASI 3 is main stream, ASI 2 is secondary stream (backup 1), ASI 1 is third stream (back up 2)	
Output	2 ASI output: ASI 4 output bypass, ASI 5 loop out ASI 3	
Interface	BNC interface	
TS Package Format	188	
ASI in/out bitrate	1~210Mbps	
System	language	English/Chinese
	Remote Control	web-server management (WEB)
	Upgrade	Web upgrade
General	Size	482mmx410mmx44mm
	Temperature	0~45°C (working); -20~80 (Storage)
	Power Supply	110VAC±10%, 50/60Hz 220VAC±10%, 50/60Hz
	Consumption	15W